


# AISSIBOXER-01

## AIR-OPERATED DOUBLE DIAPHRAGM PUMPS



**DEBEM**  
HYGIENIC SOLUTIONS



Suction/delivery connections	BS 4825 1" Clamp
Air fitting	3/8" f BSPP
Max flow rate*	100 l/min
Max air supply pressure	8 bar
Max head*	80 m
Max suction from negative head - dry running*	2,5 m
Max suction from negative head - with pump on	9,5 m
Max diameter of suspended solids	5 mm

\* The value depends on the pump configuration.



CE




- Product designed and built in Italy
- PATENTED anti-stall pneumatic circuit
- Operates with NON-lubricated air
- SELF-PRIMING
- It supports dry running
- Possibility of adjusting the operating speed
- Versatility of use
- Suitable for handling fluids with high viscosity and for heavy applications
- Possibility of handling fluids with suspended solids
- Suitable for continuous service

# AISIBOXER-01

AIR-OPERATED DOUBLE DIAPHRAGM PUMPS



## Specifications and types



\* The curves and performances refer to pumps with submerged suction and free delivery outlet, with water at 20°C and vary according to the composition materials.

Flow rate (l/min)




Air supply pressure (bar)

Air consumption (NI/min)



### Quick emptying system

A system that allows the pump to completely empty the fluid present inside the chambers.



## AISI 316 L

## AISIBOXER-01

### Maximum Dimensions

Height	618 mm
Width	436 mm
Depth	352 mm

### Construction materials (casing and manifolds) and net weight

AISI 316 L*	16 Kg
	Temp. 3°C min.
	95°C max

\*Mechanically polished - surface finish <0.8 µm